

Shank sweep en 6,35 mm (standard sweep 43°)

CODE / CÓDIGO	A		B		C		Fixing / Anclaje		F	G
	Width /		Angle		Tickness /		D		Wing	Neck
	Ancho	Inch	Attack / Ángulo	Ataque	Espesor	Inch	Bolt / Bulón	B/Centers / E/Centro	Widht / Ancho	Height / Altura
		mm				mm			mm	mm
IAR 0076-8	7"		178 43°		.315		8,00 SQ. 1/2"	57	76	110
IAR 0451	8"		203 43°		.250		6,35 SQ. 1/2"	57	76	110
IAR 0452	10"		254 43°		.250		6,35 SQ. 1/2"	57	76	110
IAR 0170	12"		305 43°		.250		6,35 SQ. 1/2"	57	76	110
IAR 0123	14"		356 43°		.250		6,35 SQ. 1/2"	57	76	110
IAR 0080	16"		406 43°		.250		6,35 SQ. 1/2"	57	76	110
IAR 0527 Stay Wide	18"		457 43°		.250		6,35 SQ. 1/2"	57	76	110
IAR 0527 Regular	18"		457 43°		.250		6,35 SQ. 1/2"	57	76	110

Shank sweep en 6,35 mm (STANDAR SWEEP 47°)

CODE / CÓDIGO	A		B		C		Fixing / Anclaje		F	G
	Width / Ancho		Angle		Tickness /		D		Wing	Neck
	Trabajo	Inch	Attack / Ángulo	Ataque	Espesor	Inch	Bolt / Bulón	B/Centers / E/Centro	Widh / Ancho del ala	Height / Altura de vaina
		mm				mm			mm	mm
IAR 0528	8"		203 47°		.250		6,35 SQ. 1/2	57 mm	76	117

IAR 0529	10"	254 47°	.250	6,35 SQ. 1/2	57 mm	76	117
IAR 0530	12"	305 47°	.250	6,35 SQ. 1/2	57 mm	76	117
IAR 0455	14"	356 47°	.250	6,35 SQ. 1/2	57 mm	76	117
IAR 0456	16"	406 47°	.250	6,35 SQ. 1/2	57 mm	76	117
IAR 0457 Stay Wide	18"	457 47°	.250	6,35 SQ. 1/2	57 mm	76	117
IAR 0457 Regular	18"	457 47°	.250	6,35 SQ. 1/2	57 mm	76	117

Shank sweep en 6.35 mm (STANDAR SWEEP 50°)

CODE / CÓDIGO	A		B Angle Attack / Ángulo Ataque	C Tickness / Espesor	Fixing / Anclaje		F Wing Widh / Ancho del ala	G Neck Height / Altura de vaina
	Width / Ancho Trabajo				D	E		
	Inch	mm						
IAR 0531	8	203	50º	.250	6,35 SQ. 1/2	57 mm	76	120
IAR 0458	10	254	50º	.250	6,35 SQ. 1/2	57 mm	76	120
IAR 0459	12	305	50º	.250	6,35 SQ. 1/2	57 mm	76	120
IAR 0532	14	356	50º	.250	6,35 SQ. 1/2	57 mm	76	120
IAR 0460	16	406	50º	.250	6,35 SQ. 1/2	57 mm	76	120
IAR 0461 Stay Wide	18	457	50º	.250	6,35 SQ. 1/2	57 mm	76	120
IAR 0461 Regular	18	457	50º	.250	6,35 SQ. 1/2	57 mm	76	120

Shank sweep en 6.35 mm (STANDAR SWEEP 55°)

CODE / CÓDIGO	A		B Angle Attack / Ángulo Ataque	C		Fixing / Anclaje		F	G
	Width / Ancho Trabajo			Tickness / Espesor	D	E	Wing	Neck	
							Widh / Ancho del ala	Height / Altura de vaina	
	Inch	mm							
IAR 0819	8	203	55°	.250	6,35	SQ. 1/2	57 mm	76	120
IAR 0820	10	254	55°	.250	6,35	SQ. 1/2	57 mm	76	120
IAR 0821	12	305	55°	.250	6,35	SQ. 1/2	57 mm	76	120
IAR 0822	14	356	55°	.250	6,35	SQ. 1/2	57 mm	76	120
IAR 0823	16	406	55°	.250	6,35	SQ. 1/2	57 mm	76	120
IAR 0824 Stay Wide	18	457	55°	.250	6,35	SQ. 1/2	57 mm	76	120
IAR 0824 Regular	18	457	55°	.250	6,35	SQ. 1/2	57 mm	76	120

Shank sweep en 8,0 mm (STANDAR SWEEP 43°)

CODE / CÓDIGO	A		B Angle Attack / Ángulo Ataque	C		Fixing / Anclaje		F	G
	Width / Ancho Trabajo			Tickness / Espesor		D	E	Wing Widh / Ancho del ala	Neck Height / Altura de vaina
	Inch	mm		Inch	mm	Bolt / Bulón	B/Centers / E/Centro	mm	mm
IAR 0559	8	203	43°	.315	8,0	SQ. 1/2	57 mm	76	110

IAR 0560	10	254	43°	.315	8,0	SQ. 1/2	57 mm	76	110
IAR 0462	12	305	43°	.315	8,0	SQ. 1/2	57 mm	76	110
IAR 0561	14	356	43°	.315	8,0	SQ. 1/2	57 mm	76	110
IAR 0463	16	406	43°	.315	8,0	SQ. 1/2	57 mm	76	110
IAR 0562 Stay Wide	18	457	43°	.315	8,0	SQ. 1/2	57 mm	76	110
IAR 0562 Regular	18	457	43°	.315	8,0	SQ. 1/2	57 mm	76	110

Shank sweep en 8.0 mm (STANDAR SWEEP 47°)

CODE / CÓDIGO	A		B Angle Attack / Ángulo Ataque	C		Fixing / Anclaje		F	G
	Width / Ancho Trabajo			Tickness / Espesor	D	E	Wing	Neck	
							Widh / Ancho del ala	Height / Altura de vaina	
	Inch	mm					Inch	mm	Bolt / Bulón
IAR 0563	8	203	47º	.315	8,0	SQ. 1/2	57 mm	76	117
IAR 0564	10	254	47º	.315	8,0	SQ. 1/2	57 mm	76	117
IAR 0565	12	305	47º	.315	8,0	SQ. 1/2	57 mm	76	117
IAR 0566	14	356	47º	.315	8,0	SQ. 1/2	57 mm	76	117
IAR 0567	16	406	47º	.315	8,0	SQ. 1/2	57 mm	76	117
IAR 0568 Stay Wide	16	406	47º	.315	8,0	SQ. 1/2	57 mm	76	117
IAR 0568 Regular	18	457	47º	.315	8,0	SQ. 1/2	57 mm	76	117

Shank sweep en 8,0 mm. (STANDAR SWEEP 50°)

CODE / CÓDIGO	A		B Angle Attack / Ángulo Ataque	C		Fixing / Anclaje		F	G
	Width / Ancho Trabajo			Tickness / Espesor		D	E	Wing Widh / Ancho del ala	Neck Height / Altura de vaina
	Inch	mm		Inch	mm	Bolt / Bulón	B/Centers 7 E/Centro	mm	mm
IAR 0569	8	203	50°	.315	8,0	SQ. 1/2	57 mm	76	120
IAR 0570	10	254	50°	.315	8,0	SQ. 1/2	57 mm	76	120
IAR 0464	12	305	50°	.315	8,0	SQ. 1/2	57 mm	76	120
IAR 0571	14	356	50°	.315	8,0	SQ. 1/2	57 mm	76	120
IAR 0465	16	406	50°	.315	8,0	SQ. 1/2	57 mm	76	120
IAR 0572 Stay Wide	18	457	50°	.315	8,0	SQ. 1/2	57 mm	76	120
IAR 0572 Regular	18	457	50°	.315	8,0	SQ. 1/2	57 mm	76	120

Shank sweep en 8,0 mm. (STANDAR SWEEP 55°)

CODE / CÓDIGO	A		B Angle Attack /Ángulo Ataque	C		Fixing / Anclaje		F	G
	Width / Ancho Trabajo			Tickness / Espesor		D	E	Wing Widh / Ancho del ala	Neck Height / Altura de vaina
	Inch	mm		Inch	mm	Bolt / Bulón	B/Centers / E/Centro	mm	mm
IAR 0819-1	8	203	55°	.315	8,0	SQ. 1/2	57 mm	76	120

IAR 0820-1	10	254 55°	.315	8,0 SQ. 1/2	57 mm	76	120
IAR 0821-1	12	305 55°	.315	8,0 SQ. 1/2	57 mm	76	120
IAR 0822-1	14	356 55°	.315	8,0 SQ. 1/2	57 mm	76	120
IAR 0823-1	16	406 55°	.315	8,0 SQ. 1/2	57 mm	76	120
IAR 0824-1 Stay Wide	18	457 55°	.315	8,0 SQ. 1/2	57 mm	76	120
IAR 0824-1 Regular	18	457 55°	.315	8,0 SQ. 1/2	57 mm	76	120