

Alabama sweep en 6,35mm

CÓDIGO	A		B	D		G	Anclaje		H
	Ancho		Largo	Espesor		Ángulo	F	C	
	Inch	mm	mm	Inch	mm	Ataque	Bulón	E/centro	mm
IAR 0806	14	356	237	.250	6,35	25°	SQ. 1/2	57,15 mm	93
IAR 0807	16	406	270	.250	6,35	25°	SQ. 1/2	57,15 mm	107
IAR 0808	18	457	304	.250	6,35	25°	SQ. 1/2	57,15 mm	111
IAR 0809	20	508	338	.250	6,35	25°	SQ. 1/2	57,15 mm	135
IAR 0810	22	559	373	.250	6,35	25°	SQ. 1/2	57,15 mm	150
IAR 0811	24	607	405	.250	6,35	25°	SQ. 1/2	57,15 mm	164

“S” TINES SWEEPS en 8,0 mm.

CÓDIGO	A		B	D		G	Anclaje		H
	Ancho		Largo	Espesor		Ángulo	F	C	
	Inch	mm	mm	Inch	mm	Ataque	Bulón	E/centro	mm
IAR 0800	14	356	237	.315	8,0	25°	SQ. 1/2	57,15 mm	93
IAR 0801	16	406	270	.315	8,0	25°	SQ. 1/2	57,15 mm	107
IAR 0802	18	457	304	.315	8,0	25°	SQ. 1/2	57,15 mm	111
IAR 0803	20	508	338	.315	8,0	25°	SQ. 1/2	57,15 mm	135
IAR 0804	22	559	373	.315	8,0	25°	SQ. 1/2	57,15 mm	150
IAR 0805	24	607	405	.315	8,0	25°	SQ. 1/2	57,15 mm	164